## EXPOSED FASTENING SYSTEMS



The Corrugated metal wall panel is ideal for a variety of market places, including residential, light commercial, agricultural and storage facilities. The Corrugated metal wall panel can be used in both vertical and horizontal applications.


## FEATURES AND BENEFITS:

• UL 790 external fire rating is available.

## **PRODUCT SPECIFICATIONS**

Applications: Roof and Wall Coverage Widths: 24" Rib Spacing: 2<sup>5</sup>/<sub>8</sub>" on center Rib Height: <sup>1</sup>/<sub>2</sub>" Minimum Slope: 3:12 Panel Attachment: Exposed Fastening System Gauges: 29 (standard); 26 (optional) Finishes: Smooth (standard) Coatings: Galvalume Plus<sup>®</sup>, Signature<sup>®</sup> 200









## EXPOSED FASTENING SYSTEMS

CATEGORY	CHARACTERISTIC	TEST METHOD	PURPOSE	RESULT
STRUCTURAL	Negative Wind Loads	AISI S100	North American Specification for the Design of Cold-Formed Steel Structural Members	See Section Properties and Allowable Load Table Section
	Gravity Loads	AISI S100	North American Specification for the Design of Cold-Formed Steel Structural Members	See Section Properties and Allowable Load Table Section

Descriptions and specifications contained herein were in effect at the time this publication was approved for printing. In a continuing effort to refine and improve products, Metallic reserves the right to discontinue products at any time or change specifications and/or designs without incurring obligation. To ensure you have the latest information available, please inquire or visit our website at www.metallic.com. Application details are for illustration purposes only and may not be appropriate for all environmental conditions, building designs or panel profiles. Projects should be designed to conform to applicable building codes, regulations and accepted industry practices. If there is a conflict between this document and project erection drawings, the erection drawings will take precedence.

