EXPOSED FASTENING SYSTEMS

WEATHERSAFE®



The WeatherSafe® panel can be used for both roof and wall applications and are ideal for residential, light commercial, agricultural and storage buildings.

FEATURES AND BENEFITS:

- WeatherSafe® is also used for canopy structures.
- WeatherSafe® is an exposed fastened system.
- The WeatherSafe® panel must be installed over a solid, waterproofed deck when used as a roof panel.
- UL 790 external ratings are available as well as UL 793 internal fire ratings.

PRODUCT SPECIFICATIONS

Applications: Roof and Wall Coverage Widths: 36"
Rib Spacing: 12" on center

Rib Height: 7/8" Minimum Slope: 3:12


Panel Attachment: Exposed Fastening System

Gauges: 29 (standard); 26 (optional)

Finishes: Smooth (standard); Embossed (optional)

Coatings: Galvalume Plus®, Signature® 200





EXPOSED FASTENING SYSTEMS

WEATHERSAFE®

CATEGORY	CHARACTERISTIC	TEST METHOD	PURPOSE	RESULT
STRUCTURAL	Negative Wind Loads	AISI S100	North American Specification for the Design of Cold-Formed Steel Structural Members	See Section Properties and Allowable Load Table Section
	Gravity Loads	AISI S100	North American Specification for the Design of Cold-Formed Steel Structural Members	See Section Properties and Allowable Load Table Section