




EXPOSED FASTENING SYSTEMS

AVP

The AVP panel is used for wall application and features pencil ribs, providing improved aesthetics to the building design.



FEATURES AND BENEFITS

- The AVP panel allows for more insulation to be added behind the panel, providing greater insulating values that meet the energy codes and R-Value requirements.
- UL 263 internal fire rating is available.

PRODUCT SPECIFICATIONS

- Applications: Wall
- Coverage Widths: 36"
- Rib Spacing: 12" on center
- Rib Height: 1-1/8"
- Panel Attachment: Exposed Fastening System
- Gauges: 26 (Standard);
 22, 24, 29 (Optional)
- Finishes: Smooth (Standard); Embossed (Optional)
- Coatings: Galvalume Plus®, Signature® 200, Signature® 300



EXPOSED FASTENING SYSTEMS

AVP

CATEGORY	CHARACTERISTIC	TEST METHOD	PURPOSE	RESULT
STRUCTURAL	Negative Wind Loads	AISI S100	North American Specification for the Design of Cold-Formed Steel Structural Members	See Section Properties and Allowable Load Table Section
	Positive Wind Loads	AISI S100	North American Specification for the Design of Cold-Formed Steel Structural Members	See Section Properties and Allowable Load Table Section

Descriptions and specifications contained herein were in effect at the time this publication was approved for printing. In a continuing effort to refine and improve products, Metallic Building Systems reserves the right to discontinue products at any time or change specifications and/or designs without incurring obligation. To ensure you have the latest information available, please inquire or visit our website at metallic.com.



PHONE 866-521-7521 EMAIL SALES@METALLIC.COM

METALLIC.COM